

New Product News

TENTATIVE

Super – Thin 15" TFT LCD Monitor with SDI Inputs for Relay and Studio Applications

TM-15L1D

15" Professional LCD Display Monitor
4:3 1024 x 768 (XGA)



TM-15L1D

Stylish Professional Design

Full Metal Cabinet ▪ Slim Bezel and Square Design ▪
Corner Protector ▪ Tough Control Keys

Easy Installation

VESA 100 Mounting Holes ▪ Screw Holes for Installation ▪
Wall Mounting Capability ▪ Built-In Power Supply ▪
Tilt and Height Adjustable Stand Provided

Professional Features

2 Line SDI Inputs (Switched Out) ▪ Various Scan Size Mode (Over/1:1/User) ▪
Easy Control Front Keys ▪ Wired Remote (Make Contact or Trigger Pulse) ▪
BNC Connector ▪ Rack Mount Capability ▪ CTI & LTI ▪
Blue Check / Color Off / Aspect ▪ Twin Color Tally (G/R) ▪ 5 Line Audio Input (Mono)

Specifications

Model		<i>TM-15L1D</i>	
Type		<i>LCD Display Monitor</i>	
Colour System		<i>PAL and NTSC</i>	
LCD Panel	Type		<i>15" Active matrix TFT</i>
	Effective Screen Size		<i>Width: 304.1 mm, Height: 228.1 mm</i>
	Pixels		<i>1024 x 768</i>
	Aspect Ratio		<i>4 : 3</i>
	Display Colours		<i>16.2 milion</i>
	Viewing angle	Horizontal	<i>140°</i>
		Vertical	<i>125°</i>
	Brightness		<i>400 cd/m²</i>
Contrast Ratio		<i>500 : 1</i>	
Input/Output Terminals	Video	Video 1	<i>Composite Video 1 line BNC x 2 (Bridged Out)</i>
		Video 2	<i>Composite Video 1 line BNC x 2 (Bridged Out)</i>
		Component	<i>D-sub 15-pin x 1 (SD)</i>
		SDI	<i>IN (BNC) x 2 ,SWITCHED OUT (BNC x 1)</i>
	Audio	Video	<i>IN (RCA) x 2</i>
		Component	<i>IN (RCA) x 1</i>
		SDI	<i>IN (RCA) x 2</i>
		Audio Output	
Environmental Conditions		<i>Operating temperature: 5°C to 35°C</i>	
		<i>Operating humidity: 20 % to 85 % (non condensing)</i>	
Power Requirements		<i>AC 100-240 V, 50 Hz/60 Hz</i>	
Power Consumption		<i>0.9 A</i>	
Dimentions (WxDxH)	<i>without stand</i>		<i>342 x 291 x 70.5 mm</i>
	<i>with stand (low position)</i>		<i>342 x 295.6 x 184 mm</i>
	<i>with stand (high position)</i>		<i>342 x 330.6 x 184 mm</i>
Weight	<i>excluding stand</i>		<i>36 kg</i>
	<i>including stand</i>		<i>62 kg</i>
Provided Accessory		<i>AC Power Cord, BNC ->D-sub Transform cable, Stand</i>	

Input Signals

INPUT	FORMAT or SYSTEM
VIDEO	<i>NTSC PAL</i>
COMPONENT	<i>480/60i 576/ 50i</i>
SD SDI	<i>480/60i 576/ 50i D1 Serial Digital Signal</i>
AUDIO	<i>Analog mono LINE IN</i>
Wired Remote (RJ45)	<i>MAKE Contact or TRIGGER Pulse system</i>

Input Terminal



DISTRIBUTED BY

JVC

E.& O.E. Design and specifications subject to change without notice.

All brand or product names may be trademarks and/ or registered trademarks of their respectiv owners.

Any rights not expressly granted herein are reserved.

Certain accessories may not be available in certain areas.

„JVC“ is the trademark or registered trademark of Victor Company of Japan, Limited.