



X5-Lite High Performance LED On-Board Camera Light

PROSeries

The X5-Lite is a professional LED on-board camera light utilizing the latest LED technology. Providing high-output, long-lasting and consistent light output, the X5-Lite uses minimal power consumption keeping both the light, battery and camera running for as long as possible.

Advantages of LED Technology:

- **Very low power consumption** of 12W, producing the equivalent light output of a 50W halogen bulb at 5600-degrees K.
- **Minimal heat output from the LEDs** ensures light quality remains completely unaffected.
- **Extremely long life** with 10,000 hours of light.
- **Eliminates the use of bulbs**, either for replacement or the carrying of spares.
- **LEDs are protected** by a sealed scratch resistant lens, making the X5-Lite suitable for outdoor use.

X5-Lite Product Features:

- **Fully adjustable light dimmer** (constant 5600K Daylight).
- **Includes 2 pin D-Tap** power connector.
- **Camera hot-shoe for easy attachment.** The hot-shoe can remain securely fitted to the camera or tripod when the light is disconnected.
- **Stylish enclosure and compact in design**, the X5-Lite is light-weight enough for on-board camera or small tripod positioning.
- **Available as stand alone unit or as a kit with X3-BD**, detachable 4-leaf barn door & filter kit (model **X5-Kit** shown above).

Optional Accessories:

- X3-BD: Barn door assembly-filter holder, folding leaves, filter rings (3)
- X3P-C: X5-Lite shoe mount with 4-pin XLR connector
- X3P-2: X5-Lite shoe mount with 2-pin D-Tap connector (replacement)



Technical Specification

Input Voltage:
DC 11.0V ~ DC 17.0V

Power Consumption:
12W maximum

Brightness
900 lx @ 1m

Dimmer Control:
100% ~ 0%

Beam Angle:
30°

Color Temperature:
5600K Daylight

Operating Temperature:
32 - 110 degrees F

Dimensions:
2.68(W) x 4.96(H) x 4.56(D) inches

Weight:
0.67 lbs. approx.

IDX System Technology, Inc.
19001 Harborage Way, Suite 105
Torrance, CA 90501
U.S.A.
Telephone: (310) 328-2850
Fax: (310) 328-8202



For further information, email us: idx.usa@idx.tv or visit our website www.idxtek.com
IDX reserves the right to change the specifications contained herein without notice.